HIMOINSA
A YANMAR COMPANY

APOLO RANGE - MODEL

AS4006 M6

APOLO START · AS4006

Powered by YANMAR

9 meters
Maximum Height

210.000
Lumens

360º manual
Rotation

SINGLE PHASE

FREQUENCY

R.P.M.

WATER-COOLED

LED

Manual
Lifting system

DIESEL

HIMOINSA Company with quality certification ISO 9001
HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2006/95/EC Low voltage.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2012/46/EU)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2005 normative: 1000 mbar, 25ºC, 30% relative humidity.

Prime Power (PRP):
According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

HIMOINSA HEADQUARTERS:
Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 info@himoinsa.com www.himoinsa.com

Manufacture facilities:
SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA

Subsidiaries:
PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA | DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA

Index of technical icons used in this catalogue

Water-cooled	Manual	1500 1800 r.p.m.	KIT Kit	Metal halide Quartz iodine	Maximum Height
Air-cooled	Hydraulic	3000 3600 r.p.m.	360 Rotation	LED	Lumens

ISO 9001 SYSTEM CERTIFICATION

HIMOINSA
A YANMAR COMPANY

APOLO RANGE - MODEL

AS4006 M6

APOLO START · AS4006

Powered by YANMAR

Specifications

Power (P.R.P)	kVA	2,8
Voltage (2+N)	V	230
Maximum dimensions	(L x W x H)	3162 x 2781 x 9068
Minimum dimensions	(L x W x H)	3944 x 1451 x 1892
Weight	Kg	747
Fuel tank capacity	L	114
Tank refilling		External
Autonomy	Hours	207
Noise level (power at 7m)		101 LWA - 76 dB(A)

Engine Specifications 1.800 r.p.m.

Model		YANMAR 2TNV70WHR
Engine Type		4-stroke diesel
Injection Type		Indirect
Aspiration Type		Natural
Number of cylinders and arrangement		2-L
Bore and Stroke	mm	70 x 74
Displacement	L	0,57
Cooling System		Coolant
Lube Oil Specifications		SAE 3 class 10W30 / API grade CD,CF
Compression Ratio		23,4
Fuel consumption (lights only)	L/Hr	0,55
Governor	Type	Mechanical
Air Filter	Type	Dry
Inner diameter exhaust pipe	mm	40

Generator

Poles	nº	4
Connection type (standard)		Series
Mounting type		S-5 6,5"
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP21
Exciter system		Self-regulated brushless
Voltage regulator		Capacitor
Bracket type		Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnation)

ISO 9001 SYSTEM CERTIFICATION
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY

APOLO RANGE - MODEL

AS4006 M6

APOLO START · AS4006

Powered by YANMAR

Mast

Mast type		Manual
Mast sections		3
Raising / lowering time		-
Rotation		360º manual
Double safety block		Standard
Lamps	nº	4 x 350 W
Lamps type		LED
Total lumens	lm	4 x 52500 = 210.000
Remaining power	kW	1.4

Bodywork

Canopy	Standard
Retention tray	-
Auxiliary sockets	2 x 16 Amp
Auxiliary input supply socket	-
Lifting hook	Standard

Chassis

Chassis traction kit	Standard
Signalling lamps	Reflectors (rear light kit optional)
Wheels	2 x 165R13
Stabilisers	4
Bracket holders	Standard

Control panel

Control and protection panel	M7T manual controller
Thermal magnetic switches to protect the spotlights and auxiliary sockets	Standard
Manoeuvring push buttons	

ISO 9001 SYSTEM CERTIFICATION
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY

HIMOINSA
A YANMAR COMPANY

APOLO RANGE - MODEL

AS4006 M6

APOLO START · AS4006

Powered by YANMAR

Dimensions



Maximum dimensions	(L x W x H)	3162 x 2781 x 9068
Minimum dimensions	(L x W x H)	3944 x 1451 x 1892

DIMENSIONS CORRESPOND TO THE TOWERS MOUNTED WITH FLOODLIGHTS

* Amounts related to dismantled towers	6 Units *	18 Units *	18 Units *

Light range



ISO 9001 SYSTEM CERTIFICATION
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY

APOLO RANGE - MODEL

AS4006 M6

APOLO START · AS4006

Powered by YANMAR

Features

Lighting tower

· Emergency stop
· Wide accesses for maintenance and control
· 4 stabilizers, two of which are extensible to guarantee stability
· Bubble level located at the top of the genset
· Draw bar with ball coupling
· Includes lifting hooks and bracket holders
· Rings for fixation during transport
· Wheels: 2 x 165R13
· Extensible and tilting mast

Optional : · Electrical connections for signalling lights (brakes lights, turning lights), reflectors and hand brake

Electric System of the Lighting Tower

· M7T controller
· Watertight panel, for control, protection and managing
· Thermal magnetic switches for spotlights and auxiliary sockets
· Two 16 amps auxiliary power sockets for the supply of power to auxiliary equipment

Himoinsa has the right to modify any feature without prior notice.
Weights and dimensions based on standard products. Illustrations may include optional equipment.
Technical data described in this catalogue correspond to the available information at the moment of printing.
Industrial design under patent.

Local Distributor

ISO 9001 SYSTEM CERTIFICATION
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY

M7T Control Panel

MULTILINGUAL CONTROL PANEL

- Single-phase voltage
- Current (A)
- Frequency (Hz)
- Active, apparent power (kW, kVA)
- Oil pressure and water temperature (kPa, ºC)
- Battery voltage, battery charging alternator voltage (V)
- Engine Speed (rpm)

ENGINE ALARMS

- High coolant temperature
- Low oil pressure
- Battery charge alternator failure
- Start failure
- Low water level
- Overspeed
- Underspeed
- Low battery voltage
- High coolant temperature (analogue)
- Low oil pressure (analogue)
- Low fuel level
- Unexpected shutdown
- Stop failure
- Emergency stop

GENERATOR ALARMS

- Overload
- Over-voltage
- Under-voltage
- Over-frequency
- Under-frequency
- Over-current
- Inverse power
- Emergency stop

ISO 9001 SYSTEM CERTIFICATION
Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail:info@himoinsa.com | www.himoinsa.com
HIMOINSA A YANMAR COMPANY