HIMOINSA
A YANMAR COMPANY

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN



- OPEN SKID
- WATER-COOLED
- THREE PHASE
- 50 HZ
- DIESEL

Generating Rates

SERVICE		PRP / DCP	ESP
Power	kVA	1152	1276
Power	kW	921	1021
Rated Speed	r.p.m.	1.500	
Main voltage	V	400/230	
Rated at power factor	Cos Phi	0,8	

HIMOINSA Company with quality certification ISO 9001
HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2020 normative: 1000 mbar, 25ºC, 30% relative humidity.

Limited-time running power (LTP):
According to Standard ISO 8528-1:2020, this is the maximum power available for a limited operating time of 500 Hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

Emergency Standby Power (ESP):
According to ISO ISO 8528-1:2020, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

Data Center Power (DCP): Complies with Uptime Institute. The manufacturer declares an acceptable average load factor 100% for an unlimited number of hours. If the model is for DCP application, you have to inform to factory.

"Class G2" performance according to the load impact test according to ISO 8528-5:2020

HIMOINSA HEADQUARTERS:
Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 | info@himoinsa.com | www.himoinsa.com
Manufacture facilities:
SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA
Subsidiaries:
PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA | DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA

HIMOINSA
A YANMAR COMPANY

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN

Engine Specifications 1.500 r.p.m.

ENGINE		PRP / DCP	ESP
Rated Engine Output	kW	972	1073
Manufacturer		BAUDOUIN	
Model		12M33G1250.5	
Engine Type		4-stroke diesel	
Injection Type		Direct	
Aspiration Type		Turbocharged and after-cooled	
Number of cylinders and arrangement		12-V	
Bore and Stroke	mm	150 x 185	
Displacement	L	39,2	
Cooling System		Liquid (water + 50% glycol)	
Lube Oil Specifications		API CI-4 or ACEA E7	
Compression Ratio		15 : 1	
Lube oil consumption with full load		0,3 % of fuel consumption	
Total oil capacity including tubes, filters	L	160	
Total coolant capacity	L	83	
Governor	Type	Electrical	
Air Filter	Type	Dry	
Inner diameter exhaust pipe	mm	200	

Generator

Generator		
Manufacturer		STAMFORD
Poles	No.	4
Connection type (standard)		Star
Mounting type		S-0 18"
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter system		Brushes
Voltage regulator		A.V.R. (Electronic)
Bracket type		Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnation)

ISO 9001 SYSTEM CERTIFICATION
HIMOINSA CHINA CO. LTD - TLF. +86 519 8622 66 88 | FAX: +86 519 86 22 66 87 | E-mail: china@asia.himoinsa.com
Nº 10 FENGMING ROAD, SOUTH PART OF WUJIN, HI-TECH INDUSTRIAL DEVELOPMENT ZONE
CHANGZHOU 213164 JIANGSU PROVINCE P.R. CHINA
HIMOINSA A YANMAR COMPANY

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN

Application Data

Exhaust System		
Maximum exhaust temperature	ºC	550
Exhaust Gas Flow	m^3/min	204,6
Maximum allowed back pressure	mbar	75

Necessary Amount Of Air		
Cooling Air Flow	m^3/s	35
Alternator fan air flow	m^3/s	1,95

Starting System		
Starting power	kW	10
Starting power	CV	13,6

Fuel System		
Fuel Oil Specifications		Diesel
Fuel Tank	L	0
Fuel Consumption ESP	l/h	262,6
Fuel Consumption 100% PRP	l/h	236,2
Fuel Consumption 70 % PRP	l/h	163,9
Fuel Consumption 50 % PRP	l/h	119,5

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN

Dimensions



Weight and Dimensions		
(L) Length	mm	4.810
(H) Height	mm	2.520
(W) Width	mm	2.210
Maximum shipping volume	m^3	26,79
(*) Weight with liquids in radiator and sump	kg	8.280

(*) (with standard accessories)

STANDARD VERSION

Himoinsa China has the right to modify any feature without prior notice.
Weights and dimensions based on standard products. Illustrations may include optional equipment.
Technical data described in this catalogue correspond to the available information at the moment of printing.
Industrial design under patent.

Local Distributor

HIMOINSA
A YANMAR COMPANY

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN

Generator set features

Engine

· Low coolant level sensor
· Exhaust gas compensator
· Diesel engine
· 4-stroke cycle
· Water-cooled
· 24V electrical system
· Standard air filter
· Standard fuel filter
· Standard oil filter
· Radiator with pusher fan
· HTW sender
· LOP sender
· Electronic governor
· Hot parts protection
· Moving parts protection

Alternator

· Self-excited and self-regulated
· 4 poles
· AVR governor
· IP23 protection
· H class insulation

Electrical system

· Electric control and power panel with measurements devices and control unit (according to necessity and configuration)
· Connection panel wired to the safety protection (open thermal magnetic protection and alarm)
· Maintenance-free and anti-explosion battery
· Battery Switch
· Battery charger (standard on gensets with automatic control panels)
· Water Jacket Heater with single phase pump
· Battery charger alternator with ground connection
· Starter battery/ies installed (cables and bracket included)
· Ground connection electrical installation with connection ready for ground spike (not supplied)

Open set version

· Steel chassis
· Emergency stop button
· Oil sump extraction kit
· Anti-vibration shock absorbers
· Chassis with integrated fuel tank
· Fuel level gauge
· Fuel tank drain plug

HIMOINSA CHINA CO. LTD - TLF. +86 519 8622 66 88 | FAX: +86 519 86 22 66 87 | E-mail: china@asia.himoinsa.com
Nº 10 FENGMING ROAD, SOUTH PART OF WUJIN, HI-TECH INDUSTRIAL DEVELOPMENT ZONE
CHANGZHOU 213164 JIANGSU PROVINCE P.R. CHINA

HIMOINSA
A YANMAR COMPANY

MODEL
HBW-1145 T5
HEAVY RANGE
Open Skid
Powered by BAUDOUIN

PDF Summary

Created : 19/01/2026 10:59
Author : Himoinsa
Number of pages : 6
Report Type: Data Sheet - Heavy range
Generated by: HIMOINSA Engineering Dept.

Page 1. Genset data
Page 2. Engine Specifications. Generator Specifications.
Page 3. Installation Data
Page 4. Dimensions
Page 5. Generator Features & Options
Page 6. PDF Summary

