
HIMOINSA
A YANMAR COMPANY

MODEL

HGS-1030 T6 LPG

HEAVY RANGE
Open Skid
Powered by GUASCOR



- OPEN SKID
- WATER-COOLED
- THREE PHASE
- 60 HZ
- LPG

Generating Rates

Volts	Rated at power factor	Standby KVA	Standby KW	Prime KVA	Prime KW	COP KW	COP KVA
480/277 V	**1**					**1032,9**	**1032,9**
480/277 V	**0,8**					**1015,8**	**1269,7**

Available Voltages= 208/120 - 220/127 - 240/138 - 416/240 - 440/254 - 460/265.

HIMOINSA Company with quality certification ISO 9001
HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2020 normative: 1000 mbar, 25ºC, 30% relative humidity.

Limited-time running power (LTP):
According to ISO ISO 8528-1:2020, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):
According to ISO ISO 8528-1:2020, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

Continuous Power (COP): According to Standard ISO 8528-1:2020, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

"Class G2" performance according to the load impact test according to ISO 8528-5:2020

HIMOINSA HEADQUARTERS:
Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 | info@himoinsa.com | www.himoinsa.com
Manufacture facilities:
SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA
Subsidiaries:
PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA | DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA

MODEL
HGS-1030 T6 LPG
HEAVY RANGE
Open Skid
Powered by GUASCOR

Engine Specifications 1.800 r.p.m.

ENGINE		COP
Rated Engine Output	kW	1067
Manufacturer		GUASCOR
Model		G.56SM
Engine Type		4-stroke Otto Cycle
Injection Type		Carburization
Aspiration Type		Turbocharged
Number of cylinders and arrangement		16-V
Bore and Stroke	mm	160 x 175
Displacement	L	56,3
Cooling System		Water
Lube Oil Specifications		SAE 40
Compression Ratio		9,2
Fuel Consumption 100% COP	kW	2774
Fuel Consumption 80 % COP	kW	2300
Fuel Consumption 75 % COP	kW	2163
Fuel Consumption 50 % COP	kW	1550
Fuel Consumption 25 % COP	kW	965
Lube oil consumption with full load	g/kWh	0,1
Total oil capacity	L	272
Heat dissipated by coolant	kW	855
Governor	Type	Electrical
Air Filter	Type	Semi-humid

Generator

Generator		
Manufacturer		STAMFORD
Poles	No.	4
Connection type (standard)		Star
Mounting type		S-00 18"
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Voltage regulator		A.V.R. (Electronic)
Bracket type		Double drive-shaft
Coupling system		Elastic Coupling
Coating type		Standard (Vacuum impregnation)

MODEL
HGS-1030 T6 LPG
HEAVY RANGE
Open Skid
Powered by GUASCOR

Application Data

Exhaust System		
Maximum exhaust temperature	ºC	512
Exhaust Gas Flow	kg/s	1,43
Maximum allowed back pressure	mm H_2O	450

Necessary Amount Of Air		
Alternator fan air flow	m^3/s	2,34


Starting System		
Auxiliary Voltage	Vdc	12

Fuel System		
Fuel Oil Specifications		LPG
Composition *		95% Propane
Fuel supply pressure	mbar	50 - 240
Fuel Tank	L	0

ISO 9001 SYSTEM CERTIFICATION
HIMOINSA CHINA CO. LTD - TLF. +86 519 8622 66 88 | FAX: +86 519 86 22 66 87 | E-mail: china@asia.himoinsa.com
Nº 10 FENGMING ROAD, SOUTH PART OF WUJIN, HI-TECH INDUSTRIAL DEVELOPMENT ZONE
CHANGZHOU 213164 JIANGSU PROVINCE P.R. CHINA
HIMOINSA A YANMAR COMPANY

MODEL
HGS-1030 T6 LPG
HEAVY RANGE
Open Skid
Powered by GUASCOR

Dimensions



Weight and Dimensions		
(L) Length	mm	Ask
(W) Width	mm	Ask
(*) Weight with liquids in radiator and sump	kg	Ask

(*) (with standard accessories)

STANDARD VERSION

Himoinsa China has the right to modify any feature without prior notice.
Weights and dimensions based on standard products. Illustrations may include optional equipment.
Technical data described in this catalogue correspond to the available information at the moment of printing.
Industrial design under patent.

Local Distributor

ISO 9001 SYSTEM CERTIFICATION
HIMOINSA CHINA CO. LTD - TLF. +86 519 8622 66 88 | FAX: +86 519 86 22 66 87 | E-mail: china@asia.himoinsa.com
Nº 10 FENGMING ROAD, SOUTH PART OF WUJIN, HI-TECH INDUSTRIAL DEVELOPMENT ZONE
CHANGZHOU 213164 JIANGSU PROVINCE P.R. CHINA
HIMOINSA A YANMAR COMPANY

MODEL
HGS-1030 T6 LPG
HEAVY RANGE
Open Skid
Powered by GUASCOR

Generator set features

Engine

· LPG-liquefied petrol gas engine
· 4-stroke cycle
· Water-cooled
· Radiator with pusher fan
· HTW sender
· LOP sender
· Electronic governor
· Hot parts protection
· Moving parts protection

Alternator

· Self-excited and self-regulated
· 4 poles
· IP23 protection
· H class insulation
· Double drive-shaft

Gas ramp

· Manual shut-off valve
· Gas filter
· Double solenoid valve
· High pressure regulator
· Primary pressure regulator
· Low pressure switch
· High pressure switch
· Valve (tightness) testing system
· Inlet pressure manometer
· Outlet pressure manometer
· Special Start/Stop sequence

ISO 9001 SYSTEM CERTIFICATION
HIMOINSA CHINA CO. LTD - TLF. +86 519 8622 66 88 | FAX: +86 519 86 22 66 87 | E-mail: china@asia.himoinsa.com
Nº 10 FENGMING ROAD, SOUTH PART OF WUJIN, HI-TECH INDUSTRIAL DEVELOPMENT ZONE
CHANGZHOU 213164 JIANGSU PROVINCE P.R. CHINA
HIMOINSA A YANMAR COMPANY

HIMOINSA
A YANMAR COMPANY

MODEL

HGS-1030 T6 LPG

HEAVY RANGE
Open Skid
Powered by GUASCOR

PDF Summary

Created : 18/02/2026 16:41
Author : Himoinsa
Number of pages : 6
Report Type: Data Sheet - Heavy range
Generated by: HIMOINSA Engineering Dept.

Page 1. Genset data
Page 2. Engine Specifications. Generator Specifications.
Page 3. Installation Data
Page 4. Dimensions
Page 5. Generator Features & Options
Page 6. PDF Summary

